

# BA80

## Portable Oil Test Set

- Ultra fast switch-off time ( $< 5 \mu\text{s}$ )
- Housed in a metal case for proper RFI/EMC shielding
- Measurement also of silicone-, mineral- and ester oils

The BA Breakdown Analyzer is the smallest and lightest portable oil test set its rating available. The 2.8" colour display is very bright and offers optimal readability.

For measuring modern silicon, mineral and ester oils a very fast switch-off time after flash over is crucial. The BA has the fastest switch-off time on the market available ( $< 5 \mu\text{s}$ ).

With the PC Software "BA ControlCenter" individual test procedures can be programmed and several units can be controlled and overviewed simultaneously. Test results are available in printed form, as pdf and as text files.

The unit has USB Flash Drive and a Bluetooth connection for communications between the test unit and the PC.



[www.b2hv.at](http://www.b2hv.at)

## Features

### Usability

- Low weight and compact design
- Very bright colour display
- Internal Battery
- External 12 V Supply

### Technology

- Ultra fast switch-off time ( $< 5 \mu\text{s}$ )
- Direct measurement of output voltage
- Measurement also of silicone-, mineral- and ester oils
- Housed in a metal case for proper RFI/EMC shielding

### Communications

- Bluetooth connection
- USB Flash Drive
- Intuitive control

# BA80

## Portable Oil Test Set





Type	BA80
Article number	SB5003
Output voltage	up to 80 kV rms symmetrical
Voltage measurement accuracy	±1 kV
Voltage rise rate	0.5- 10 kV/s
Resolution (displayed)	0.1 kV
Power supply	85- 264 V (47-63 Hz) and 12 V external supply
Power consumption	60 VA
Internal rechargeable battery	1 x 12 V / 7.2 Ah
Switch-off time on flashover	< 5 µs
Measurement of oil temperature	0 to 100 °C
Temperature resolution	1 °C
Display	2.8" colour (ultra bright / TFT)
Selectabel programs	VDE370-5/96, ÖVE EN 60156, IEC 60156/95, ASTM1816-04-1, ASTM1816-04-2, ASTM877-02A, ASTM977-02B, AS1767.2.1, BS EN60156, NEN 10 156, NF EN60156, PA SEV EN60156, SABS EN60156, UNE EN60156, single measurement, other standards possible
Customer-specific programs	unlimited
PC Software „BA Control Center“	included
Printer	graphical output 44 mm (dot matrix)
Interface	bluetooth
USB	USB memory stick
Operating temperature	-10° to +55 °C <small>(extended temp. range)</small>
Storage temperature	-20° to +60 °C
Relative humidity	Non condensing
Dimensions W x H x D	430 x 280 x 250 mm
Weight	22 kg incl. batteries

DHV1234 Rev03 - ENGLISH - Subject to alternations. Errors excepted. Illustrations are not binding.

### Scope of delivery

- Breakdown Analyzer BA
- Test vessel with electrodes
- PC Software „BA ControlCenter“
- Printer
- Battery
- Ring nut wrench
- Lifting stick for magnetic stirrer
- Magnetic oil stirrer
- Setting gauge 2.5 mm
- User Manual

### Additional Accessories

- GB0050 PT75 Test Vessel IEC 156 Sphere Electrode incl. Gauge 
- GB0051 PT75 Test Vessel IEC 156 Mushroom Electrode incl. Gauge 
- GB0052 PT75 Test Vessel ASTM D877 Disc Electrode incl. Gauge 
- GB0053 PT75 Test Vessel ASTM D1816 Stirrer VDE Electrode & Gauge 
- VKR0011 Transport Bag
- VKR0016 Dust Cover
- VKR0010 Rugged Transport Box
- GB0110 - GB0114 Setting gauge 1 / 2 / 2.5 / 4 / 5 mm
- GB0120 Lead for connecting vehicle cigarette lighter socket (12 V, 5 m)
- GB0103 Ribbon cartridge for printer
- GB0102 Paper roll for printer



Riedstrasse 1 | A-6833 Klaus  
+43 (0) 523 57373 | info@b2hv.at